

Process Gauges

Type 26X.34



- Solid Front/Blow-Out Back Safety Case
- Field Liquid Fillable
- Monel® Wetted Parts

Type 262.34 - Dry case
Type 263.34 - Liquid filled case

WIKA's Type 26X.34 process gauge features all of the same benefits as the popular 232.34 stainless steel wetted parts gauge, but with the added advantage of Monel® wetted parts for process media conditions that require it. WIKA Type 26X.34 is ideal for applications in several process industries including petroleum, chemical, energy, and plant construction/contracting.

Standard Features

- **Nominal Case Size:** 4½" (115 mm) & 6" (160 mm)
- **Case Material:** Black- fiberglass reinforced thermoplastic (POCAN)
- **Wetted Parts:** Monel (K500 alloy Bourdon tube; M400 socket & end cap)
- **Window Type & Material:** Acrylic
- **Removable Window:** Yes, threaded ring
- **Dial Material:** White aluminum
- **Bezel Ring Type & Material:** Threaded ring
- **Liquid Fillable Gauge:** Yes
- **Case-to-Socket O-ring Material:** Viton
- **"Other" Gaskets/O-ring Types & Materials:**
Window gasket: BUNA-N, membrane: EPDM
- **Pointer Material/Type:** Black aluminum- adjustable
- **Adjustable Pointer:** Yes, under window
- **Accuracy:** ±0.5% of span ASME B40.100 Grade 2A
- **Connection Locations:** LM (lower mount)
- **Restrictor:** Standard
- **Media Operating Temperature:** Max. 212°F
- **Ambient Operating Temperature:** -40°F to 150°F dry;
-4°F to 150°F-glycerine case fill; -40°F to 150°F- silicone case fill

Available Options

- "Dampened Movement" Option: Yes
- U-Clamp Bracket: No
- Front Flange: No (special panel mount kit available)
- Rear Flange: Yes, integral to case
- Safety Glass Window: Yes
- Instrument Glass Window (flat glass): Yes
- Drag Pointer (maximum reading indicator): Yes
- Cleaned for Use in Oxygen Service: Yes
- Panel Mount Kit: Yes
- External Zero Adjustment: Yes
- Magnetic or Inductive Contact Switches: Yes (field installable)
- Receiver Gauge scales: Yes
- Special Connection: Limited to wrench flat area

Note: For options not shown - consult your WIKA Distributor or the Factory.

Type	262.34
Datasheet	26X.34
Wetted Parts	Monel
Connection	LM
Conn. Size	½" NPT
Size	4½"
Press. Scale	PSI
30" Hg	9835016
30"-0-15 psi	9835024
30"-0-30 psi	9835032
30"-0-60 psi	9835040
30"-0-100 psi	9835059
30"-0-160 psi	9835067
30"-0-200 psi	9835075
15 psi	9835091
30 psi	9835105
60 psi	9835113
100 psi	9835121
160 psi	9835130
200 psi	9835148
300 psi	9835156
400 psi	9835164
600 psi	9835172
800 psi	9835180
1,000 psi	9835199
1,500 psi	9835202
2,000 psi	9835210
3,000 psi	9835229
5,000 psi	9835237
10,000 psi	
15,000 psi	
20,000 psi	N/A

Accessories ¹	
4½" Panel Mount ²	PM
Glycerine filling Type 263.34	263.34
Silicone filling Type 263.34	SIL
External Zero Adjustment	EXT ADJ

Items without part numbers are available - consult factory.

Additional accessories available - see "Accessories" section in back of catalog

Datasheet: 26X.34